



HEAT-SHRINKABLE TUBE VC-1

VC-1 Series radiation cross-linking low temperature resistance fire tube has function of excellent insulation,age-resistance and softness.

VC-1 series products has the characteristics of fire-resistance and shrinkable temperature of 90°C,which can be done by high heat hair-dryer.They are widely used in communication,electronic, aviation and war industry and other fields for wiring insulation, water resission, wet resission and airproof,ect.

Standard color: Black,White,Red,Yellow,Blue, Green,Grey.

Size	Inside D. Before Shrinkage(mm)	Wall Of As Supplied(mm)	Inside D. After Shrinkage(mm)	Wall Of Alter Recovered(mm)	Length Per Rol (mm)
1.0/0.5	1.4±0.3	0.2±0.05	0.4±0.1	0.40±0.05	200
1.5/0.75	1.9±0.3	0.2±0.05	0.6±0.1	0.40±0.05	200
2.0/1.0	2.4±0.3	0.25±0.05	0.9±0.1	0.45±0.1	200
2.5/1.25	2.9±0.3	0.25±0.05	1.1±0.1	0.45±0.1	200
3.0/1.5	3.4±0.3	0.25±0.05	1.4±0.1	0.45±0.1	200
3.5/1.75	3.9±0.3	0.25±0.05	1.6±0.1	0.45±0.1	200
4.0/2.0	4.4±0.3	0.25±0.05	1.8±0.1	0.45±0.1	100
4.5/2.25	4.9±0.3	0.35±0.05	1.9±0.1	0.60±0.1	100
5.0/2.5	5.4±0.3	0.35±0.05	2.3±0.2	0.55±0.1	100
6.0/3.0	6.4±0.4	0.35±0.05	2.8±0.2	0.55±0.1	100
7.0/3.5	7.4±0.4	0.35±0.05	3.3±0.2	0.55±0.1	100
8.0/4.0	8.4±0.4	0.35±0.05	3.8±0.2	0.55±0.1	100
9.0/4.5	9.4±0.4	0.35±0.05	4.3±0.2	0.55±0.1	100
10.0/5.0	10.5±0.4	0.35±0.05	4.8±0.2	0.60±0.1	100
11.0/5.5	11.5±0.4	0.35±0.05	5.3±0.2	0.60±0.1	100
12.0/6.0	12.5±0.4	0.35±0.1	5.7±0.3	0.70±0.1	100
13.0/6.5	13.5±0.4	0.35±0.1	6.2±0.3	0.70±0.1	100
14.0/7.0	14.5±0.4	0.35±0.1	6.7±0.3	0.70±0.1	100
15.0/7.5	15.5±0.5	0.35±0.1	7.2±0.3	0.70±0.1	100
16.0/8.0	16.5±0.5	0.35±0.1	7.7±0.3	0.70±0.1	100
17.0/8.5	17.5±0.5	0.35±0.1	8.2±0.3	0.70±0.1	100
18.0/9.0	19.0±0.5	0.4±0.1	8.7±0.3	0.80±0.1	100
20.0/10.0	21.0±0.5	0.5±0.1	9.7±0.3	0.90±0.1	50
22.0/11.0	22.8±0.8	0.5±0.1	10.0±1.0	0.90±0.1	50
25.0/12.5	25.8±0.8	0.5±0.1	11.0±1.0	0.90±0.1	25
28.0/14.0	28.8±0.8	0.5±0.1	13.0±1.0	0.90±0.1	25
30.0/15.0	30.8±0.8	0.5±0.1	14.0±1.0	1.00±0.2	25
35.0/17.5	35.8±0.8	0.5±0.1	16.0±1.0	1.00±0.2	25
40.0/20.0	42.0±1.5	0.5±0.1	19.0±1.0	1.00±0.2	25
50.5/25.0	51.0±1.0	0.5±0.1	24.0±1.0	1.00±0.2	25

PVC Heat Shrinking Sleeve

Material: Rigid shrinkable PVC
Used for color distinction and insulation of busbar in control panel.
To be shrinked by blower or hot water.
Maximum service temp:80℃

Item No.	Lay Flat Dimension	Convert to Dia. ϕ	Shrinkable Range	Color	Packing
HS-2.8	2.8	1.8	2.8~1.5		
HS-3	3.0	1.9	3.0~1.6		
HS-4	4.0	2.5	4.0~2.2		
HS-5	5.0	3.2	5.0~2.8		
HS-6.5	6.5	4.1	6.5~3.6	Red	
HS-8.5	8.5	5.2	8.5~4.5	White	
HS-12	12	7.6	12~6.5	Blue	
HS-15	15	10	15~5.8	Black	
HS-20	20	13	20~11		100Mtrs/ Roll
HS-30	30	19	30~16		
HS-40	40	25	40~22		
HS-50	50	32	50~28		
HS-60	60	38	60~33	(Yellow	
HS-70	70	44	70~37	Green	
HS-80	80	50	80~42	Upon	
HS-100	100	63	100~65	Request)	
HS-120	120	76	120~65		
HS-150	150	95	150~90		

